

SZ-100-36MFE

Warranty

- ◆ 1 year Manufacturer Warranty
- ◆ Warranty on Electrical Performance: 5 years 80% of power output

Manufacturing

- ◆ Original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing.
- ◆ Comprehensive module power testing.

Performance

- ◆ Upgraded efficiency and unprecedented flexibility.
- ◆ Weakened hot-spot effect, extremely low risk of micro cracks and increased stability by shingle-tech.
- ◆ Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- ◆ IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m2, TC=25°C

| | |
|------------------------------|----------------------------|
| Nominal Power | 100W |
| Cell Type | Monocrystalline |
| Cell Efficiency | 22.00% |
| Maximum Power Current (Impp) | 5.35A |
| Maximum Power Voltage (Vmpp) | 18.72V |
| Open-circuit Voltage (Voc) | 22.25V |
| Short-circuit Current (Isc) | 5.67A |
| Maximum System Voltage | 100V |
| Output Tolerance | ±3% |
| Cable | 700mm / 2.5mm ² |
| Connector Type | MC4 / MC4 Compatible |
| Module Structure | ETFE/ EVA / Backsheet |
| Junction box rating | ≥IP67 |
| Number of Diodes | One |
| Working Temperature | -20°C~+65°C |

Packaging

| | |
|-------------------------|----------------|
| Module Dimensions | 1160*450*2mm |
| Module Weight | 2.05kg |
| Package | Single Package |
| Pieces per Pallet | 60 |
| Gross Weight per Pallet | 171 kg |
| Pallet Dimensions | 1.2*1.1*0.65mm |

SOLMAX NEW ENERGY B.V.

Address: Zonnebaan 23, 3542 EB Utrecht, the Netherlands

Email: info15@solarfam.nl

